



### TECHNICAL DATA SHEET

# **Hardener 3**

**Type of Adhesive** Crosslinker for water-based adhesives.

**Product Benefits** Improves the heat resistance of the bonding.

**Typical Applications** This product is suitable for water-based adhesives like PU, vinyl and

acrylic.

Suitable substrates Not applicable.

### **Typical Properties**

Last Updated: 6/22/2016

Property	Value
Base	isocyanate
Colour	colourless, liquid
Isocyanate content	approx. 22%
Solid content	100%
Density at 20°C	approx. 1.15 g/cm3
Viscosity (Brookfield, 20°C)	approx. 1 100 mPa.s
Shelf life	6 months







### **TECHNICAL DATA SHEET**

## **Hardener 3**

**Application Instructions** This product is determined on the basis of 3 to 5.5% by volume or by

weight.

The incorporation in the adhesive must be made progressively under

stirring.

Stir well the mixture before using.

**Cleaning Instructions** Please contact your local Sales Office for available cleaning solutions.

**Typical Packaging** Please contact your local Sales Office for available packaging options.

Storage Conditions In original sealed packaging protected from sun, dust, moisture and

high temperatures. Clean and dry conditions above 10°C and below

35°C. Sensitive to cold and moisture.

**Disposal Advice** Please refer to the MSDS for disposal instructions.

**Safety Advice** Please refer to the MSDS for safety advice.

#### Our Focus is Clear. Perfecting Adhesives.

IMPORTANT: The information, specifications, procedures and recommendations herein (together "information") are based on our experience and we believe these to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or thatthe information will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.



NOTE TO USER: by ordering/receiving product you accept the H.B. Fuller General Terms and Conditions of Sale applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, the total aggregate liability of H.B. Fuller for any claim or series of related claims however arising, in contract, tort (including negligence), breach of stautory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply.

H.B. Fuller Company

info-europe@hbfuller.com www.hbfuller.com/ eimea/contact-us

Nothing in any term shall operate to exclude or limit H.B. Fuller's liability for fraud, gross negligence or for death or personal injury caused by negligence or for breach of any mandatory implied terms.

